

SILICONE FOR GASKETS

PRODUCT DESCRIPTION

A colorless release agent and lubricant based on silicone oils. Widely used for long-lasting lubrication, protection, care, and impregnation of surfaces made of rubber, metal, and plastic.

APPLICATION

- › A versatile product for home, garden and workshops;
- › Lubrication of rubber seals on doors, windows and garage doors;
- › Perfect for maintaining plastic roller blinds, lubricating window fittings, tilt rollers, and sectional garage doors;
- › Car maintenance: rubber door seals, trunk lid seals, and sunroof seals, plastic parts, tires, wipers, seat belt retractor mechanism;
- › Home and garden: Refrigerator seals, strollers, shears, pruners, lawnmowers, tents, tarpaulins, etc.;

PRODUCT PROPERTIES

- › Increases rubber elasticity and refreshes color;
- › High-performance, multi-functional;
- › Protects, impregnates and lubricates;
- › Eliminates creaking and cracking sounds when rubbing plastic and metal surfaces;
- › Does not cause corrosion;
- › Waterproof and weatherproof;
- › Creates a separating film with antistatic properties.

TECHNICAL PARAMETERS

State of matter	aerosol, liquid
Colour	transparent
Smell	characteristic
Density	0,75 ± 0,05 g/cm ³
Temperature resistance:	-35°C - +160 °C
Solubility:	

Technical Data Sheet (TDS) SILICONE FOR GASKETS

a) in the water	insoluble
b) in organic solvents	soluble

The above table is for informational purposes only

DELIVERY FORM | PACKAGE

Can, 150 ml

DIRECTIONS FOR USE

Before use, read the product label. Shake well before use. Apply the product to clean, dust-free, and dry surfaces to be lubricated or protected. The product is suitable for metal, plastic, common rubber, and other materials (test before use). Excess product can be removed with a soft cloth. The product can also be applied to a cloth and wiped over the protected surfaces. Do not use on live equipment.

STORAGE AND EXPIRY DATE

The product should be stored in a closed container, upright, in a dry, cool, and well-ventilated place, away from direct sunlight and other sources of heat and ignition. Storage temperature: +5°C to +35°C (room temperature recommended). Expiration date: 2 years from the date of production. The production date is located on the bottom of the packaging.

With the publication of this data sheet, all previous editions become invalid. Release: 03.25

The product information contained in the technical data sheet is the result of conducted research. With regard to the possibility of using the product (point 3 of this technical data sheet), they should be treated only as recommendations resulting from the manufacturer's experience. Due to the numerous application possibilities and a wide range of work methods using the product, the Manufacturer does not bear any responsibility in this respect, and in particular is not responsible for the consequences of improper use of the product or the effects of work involving the product. Product information is valid only in its most current version.

RYTM TRADE Sp. z o.o.
ul. Strefowa 14
43-100 Tychy | Poland
Tel.: +48 32 324 00 60 /61

WWW.RYTMTRADE.COM



Technical Data Sheet (TDS)
SILICONE FOR GASKETS