

## SILICONE SPRAY

### PRODUCT DESCRIPTION

Silicone Spray is a colorless release agent and lubricant based on silicone oils. It is widely used for the long-lasting lubrication, protection, care, and impregnation of surfaces made of rubber, metal, and plastic.

### APPLICATION

- › Lubrication of doors, windows, and garage doors: ideal for maintaining plastic roller shutters, rubber door and window seals, and for lubricating window fittings, tilt rollers, and sectional garage doors. Car maintenance: rubber door seals, trunk lid seals, and sunroof seals, plastic parts, tires, wipers, seat belt retractor mechanism
- › Home and garden: Refrigerator seals, strollers, shears, pruners, lawnmowers, tents, tarpaulins, etc.
- › Industry: Release agent in plastic casting, injection and extrusion processes.

It facilitates the insertion of plastic and rubber profiles, e.g., in door and window construction. It is used as an assembly spray, for example, for hoses, pipes, O-rings, connectors, etc. In the paper and woodworking industries, the lubricant is used to prevent paper, wood, or adhesive residues from sticking to presses and machines. It is also used for the maintenance of conveyor belts.

### PRODUCT PROPERTIES

- › High-performance, multi-purpose silicone spray;
- › Protects, impregnates and lubricates;
- › Eliminates creaking and cracking sounds when rubbing plastic and metal surfaces;
- › Temperature resistance from -30°C to +160°C;
- › Does not cause corrosion;
- › Waterproof and weatherproof;
- › Creates a separating film with antistatic properties.

### TECHNICAL PARAMETERS

Colour	colorless
Smell	characteristic
State of matter	aerosol, liquid
Density	0,75 ± 0,05 g/cm <sup>3</sup>

## Technical Data Sheet (TDS)

### SILICONE SPRAY

Temperature resistance	-30°C ÷ +160°C
pH value	not applicable
Solubility:	
a) in the water	insoluble
b) in organic solvents	soluble

*The above table is for informational purposes only*

## DELIVERY FORM | PACKAGE

Can, 400 ml

## DIRECTIONS FOR USE

Before use, read the product label. Shake well before use. Apply the product to clean, dust-free, and dry surfaces to be lubricated or protected. The product is suitable for metal, plastic, common rubber, and other materials (test before use). Excess product can be removed with a soft cloth. The product can also be applied to a cloth and wiped over the protected surfaces. Do not use on live equipment.

## STORAGE AND EXPIRY DATE

The product should be stored in a closed container, upright, in a dry, cool, and well-ventilated place, away from direct sunlight and other sources of heat and ignition. Storage temperature: +5°C to +35°C (room temperature recommended). Expiration date: 2 years from the date of production. The production date is located on the bottom of the packaging.

*With the publication of this data sheet, all previous editions become invalid. Release: 02/25*

The product information contained in the technical data sheet is the result of conducted research. With regard to the possibility of using the product (point 3 of this technical data sheet), they should be treated only as recommendations resulting from the manufacturer's experience. Due to the numerous application possibilities and a wide range of work methods using the product, the Manufacturer does not bear any responsibility in this respect, and in particular is not responsible for the consequences of improper use of the product or the effects of work involving the product. Product information is valid only in its most current version.

**RYTM TRADE Sp. z o.o.**  
 ul. Strefowa 14  
 43-100 Tychy | Poland  
 Tel.: +48 32 324 00 60 /61

**WWW.RYTMTRADE.COM**