

## POLYURETHANE FOAM CLEANER

### PRODUCT DESCRIPTION

A highly effective, fast-acting cleaner for cleaning uncured PU foams and adhesives. Essential for cleaning application guns and degreasing surfaces before applying paints, adhesives, and sealants.

### APPLICATION

- › A product for cleaning guns after applying polyurethane foams and adhesives;
- › Reliably and quickly dissolves fresh foam and polyurethane adhesives, helping to remove them from most surfaces;
- › Includes an additional spray head for external cleaning of foam guns and other surfaces;

### PRODUCT PROPERTIES

- › Prevents foam guns from clogging after application, ensuring long-term use of the guns when cleaned regularly;
- › It can also be used as a cleaner for larger surfaces thanks to the included spray head;
- › An excellent agent for degreasing steel surfaces before applying polyurethanes and silicones;
- › The 360° valve allows operation in any position;

### TECHNICAL PARAMETERS

Colour	transparent
Smell	characteristic
Density	0,79 ± 0,04 g/cm <sup>3</sup>
State of matter	aerosol, liquid
Solubility:	
a) in the water	soluble
b) in organic solvents	soluble

*The above table is for informational purposes only*

### DELIVERY FORM | PACKAGE

Can, 500 ml



## Technical Data Sheet (TDS) PU FOAM CLEANER

### DIRECTIONS FOR USE

**For removing fresh polyurethane foam:** Fresh foam splatters can be removed effortlessly. Place the spray head on the valve and press lightly. Direct the spray directly onto the dirty area. When cleaning delicate surfaces, always test in an inconspicuous area. Thoroughly wipe off the dissolved PU foam with an absorbent cloth.

**Cleaning the assembly gun:** Clean the outside of the assembly gun with the spray head attached. Then remove the spray head and screw the can onto the assembly gun socket. Carefully press the spray gun trigger. As soon as the cleaning agent comes out of the gun tip, release the trigger. Let it sit for 3 minutes and then press the gun trigger twice more to remove the contents from the inside. Unscrew the can from the gun and press the trigger again.

**CAUTION!** Cured foam can only be removed mechanically. Do not clean the assembly gun with sharp or pointed objects. PU cleaner may damage or discolor the substrate (e.g., paints, plastics, textiles). For professional use only.

### STORAGE AND EXPIRY DATE

The product should be stored in a closed container, upright, in a dry, cool, and well-ventilated place, away from direct sunlight and other sources of heat and ignition. Storage temperature: +5°C to +35°C (room temperature recommended). Expiration date: 2 years from the date of production. The production date is located on the bottom of the packaging.

### WARNINGS

Repeated exposure may cause skin dryness or cracking. Inadequate ventilation may result in the formation of explosive mixtures. Contains acetone.

*With the publication of this data sheet, all previous editions become invalid. Release: 03.25*

The product information contained in the technical data sheet is the result of conducted research. With regard to the possibility of using the product (point 3 of this technical data sheet), they should be treated only as recommendations resulting from the manufacturer's experience. Due to the numerous application possibilities and a wide range of work methods using the product, the Manufacturer does not bear any responsibility in this respect, and in particular is not responsible for the consequences of improper use of the product or the effects of work involving the product. Product information is valid only in its most current version.

**RYTM TRADE Sp. z o.o.**  
ul. Strefowa 14  
43-100 Tychy | Poland  
Tel.: +48 32 324 00 60 /61

**WWW.RYTMTRADE.COM**