

MULTIPLUS X5 MULTIFUNCTIONAL OIL

PRODUCT DESCRIPTION

A universal, multi-purpose mineral oil-based oil for five applications: lubrication, cleaning, corrosion protection, rust removal, and electro-contact spray.

APPLICATION

- › Loosens rusty screws, pipe fittings, nuts, joints, Bowden cables, shafts, locks, etc.;
- › Infiltrates and displaces moisture in electrical areas;
- › Prevents corrosion of metals and electrical assemblies, cable connections, relays, plugs, connectors, etc.;
- › Prevents icing of lock cylinders and locks;
- › Lubricates locks, hinges, bushings, chains, door latches, window fittings, tilt rollers, and sectional garage doors;
- › Eliminates squeaking and allows anything that is blocked or jammed to slide smoothly;
- › Cleans and maintains plastic and metal parts such as panels and housings.

PRODUCT PROPERTIES

- › Universal, versatile use;
- › Good protection against corrosion;
- › Keeps moving parts in working order;
- › Neutral towards plastics, paints, metals and wood;
- › Reduces friction and wear;
- › Loosens rust;
- › Lubricates and preserves;
- › Dissolves dirt;
- › Improves electrical conductivity;
- › High load resistance;
- › Acid-free, silicone-free and n-hexane-free.

TECHNICAL PARAMETERS

Colour	transparent, yellowish
Smell	characteristic

Technical Data Sheet (TDS)

MULTIPLUS X5

State of matter	aerosol, liquid
Density	0,76 - 0,85 g/cm ³
Temperature resistance	-30°C ÷ +130°C
pH value	not applicable
Solubility:	
a) in the water	insoluble
b) in organic solvents	soluble

The above table is for informational purposes only

DELIVERY FORM | PACKAGE

Can, 400 ml

DIRECTIONS FOR USE

Before use, read the product label. Shake the can vigorously before use. For optimal results, first mechanically clean the affected area to remove any dirt. Apply a thin, even layer to the surfaces to be lubricated or protected. Allow to work, depending on the required penetration depth. Repeat application if necessary.

CAUTION! Do not use the product on hot surfaces or components connected to a power source. Remember to disconnect devices from the mains when using the product and, before reconnecting them to the mains, blow out closed systems with compressed air. Test plastic components for surface resistance to the product.

STORAGE AND EXPIRY DATE

The product should be stored in a closed container, upright, in a dry, cool, and well-ventilated place, away from direct sunlight and other sources of heat and ignition. Storage temperature: +5°C to +35°C (room temperature recommended). Expiration date: 2 years from the date of production. The production date is located on the bottom of the packaging.

With the publication of this data sheet, all previous editions become invalid. Release: 02/25

The product information contained in the technical data sheet is the result of conducted research. With regard to the possibility of using the product (point 3 of this technical data sheet), they should be treated only as recommendations resulting from the manufacturer's experience. Due to the numerous application possibilities and a wide range of work methods using the product, the Manufacturer does not bear any responsibility in this respect, and in particular is not responsible for the consequences of improper use of the product or the effects of work involving the product. Product information is valid only in its most current version.

RYTM TRADE Sp. z o.o.
 ul. Strefowa 14
 43-100 Tychy | Poland
 Tel.: +48 32 324 00 60 /61

WWW.RYTMTRADE.COM