

LUBRICANT FOR WINDOW AND DOOR FITTINGS

PRODUCT DESCRIPTION

Fittings lubricant is a special product for the maintenance and care of door and window mechanics, such as hinges, corners, and connectors equipped with bolts or pins, handles, and catches.

APPLICATION

- › Designed for lubrication and maintenance of mechanical moving parts, hinges, window and door handles, guides, locks, cylinder inserts, springs, etc.;
- › Quickly loosens jammed or seized mechanisms;
- › Contains additives that ensure constant ease of movement and minimize wear on moving parts;
- › Preservation and protection of interior and exterior metal surfaces;
- › High material compatibility with additional protective effect;

PRODUCT PROPERTIES

- › Colorless, odorless;
- › Excellent adhesion to all types of metals;
- › Protects against moisture and corrosion;
- › Reduces friction and eliminates squeaking;
- › Long-lasting effect;
- › Antistatic effect;
- › Free from resins, acids and silicone;
- › Leaves a long-lasting, waterproof protective film;

TECHNICAL PARAMETERS

Colour	transparent
Smell	characteristic
State of matter	aerosol, liquid
Density	0,85 ± 0,05 g/cm ³

Technical Data Sheet (TDS)

PREPARATION FOR LUBRICATION AND MAINTENANCE OF DOOR AND WINDOW MECHANICS

Temperature resistance	-15°C ÷ +110°C
pH value	not applicable
Solubility:	
a) in the water	insoluble
b) in organic solvents	soluble

The above table is for informational purposes only

DELIVERY FORM | PACKAGE

Can, 400 ml

DIRECTIONS FOR USE

Before use, read the product label. Shake well before use. Apply the product to clean, dust-free, and dry surfaces to be lubricated or protected. The product is suitable for metal, plastic, common rubber, and other materials (test before use). Excess product can be removed with a soft cloth. The product can also be applied to a cloth and wiped over the protected surfaces. Do not use on live equipment.

STORAGE AND EXPIRY DATE

The product should be stored in a closed container, upright, in a dry, cool, and well-ventilated place, away from direct sunlight and other sources of heat and ignition. Storage temperature: +5°C to +35°C (room temperature recommended). Expiration date: 2 years from the date of production. The production date is located on the bottom of the packaging.

With the publication of this data sheet, all previous editions become invalid. Release: 11.24

The product information contained in the technical data sheet is the result of conducted research. With regard to the possibility of using the product (point 3 of this technical data sheet), they should be treated only as recommendations resulting from the manufacturer's experience. Due to the numerous application possibilities and a wide range of work methods using the product, the Manufacturer does not bear any responsibility in this respect, and in particular is not responsible for the consequences of improper use of the product or the effects of work involving the product. Product information is valid only in its most current version.

RYTM TRADE Sp. z o.o.
 ul. Strefowa 14
 43-100 Tychy | Poland
 Tel.: +48 32 324 00 60 /61

WWW.RYTMTRADE.COM