

ADHESIVE AND LABEL REMOVER

PRODUCT DESCRIPTION

A special cleaner for the effective and quick removal of adhesive residue, stickers, labels, and adhesive tapes, as well as oil, grease, resin, and tar. Its easy application makes it versatile and highly effective.

APPLICATION

- › Perfect for wherever removing self-adhesive labels is a problem;
- › Reliably removes residues of most adhesives and adhesive tapes;
- › Allows easy removal of labels and stickers;
- › Removes grease, tar, and resin residue, and easily removes heel marks, rubber marks, and some dye and ink stains;
- › The solvent contained in it softens the adhesive layer and allows it to be removed.

PRODUCT PROPERTIES

- › Precise and economical dosing thanks to the fine spray jet;
- › Suitable for surfaces such as glass, metal, wood, PVC, foil, and all non-sensitive surfaces;
- › Evaporates without leaving any traces, leaving a pleasant scent;
- › Reaches even hard-to-reach places;
- › Be careful when using on polystyrene, varnished wood, and other sensitive surfaces.

Test the product on an inconspicuous area first;

- › No silicone

TECHNICAL PARAMETERS

Colour	transparent
Smell	characteristic
State of matter	aerosol, liquid
Density	0,79 ± 0,05 g/cm ³
Solubility:	
a) in the water	insoluble
b) in organic solvents	soluble

The above table is for informational purposes only



Technical Data Sheet (TDS) ADHESIVE AND LABEL REMOVER

DELIVERY FORM | PACKAGE

Can, 400 ml

DIRECTIONS FOR USE

Apply directly to the adhesive residue, label, or sticker, leave for approximately 3-5 minutes, and then peel the label off the surface or wipe off the dissolved adhesive residue. Once all residue is removed, the surface is ready for new labels. In difficult cases, the application time can be extended to approximately 15 minutes. If adhesive residue remains after removing the label, spray onto a cloth and wipe off the residue.

ATTENTION

Before using on plastics or painted surfaces, it is essential to test their suitability (resistance test). The adhesive and label remover is not suitable for items made of polystyrene or polycarbonate. It has a strong cleaning and degreasing effect. When using in large quantities, wear appropriate protective gloves to avoid skin irritation. The work area must be well ventilated.

STORAGE AND EXPIRY DATE

The product should be stored in a closed container, upright, in a dry, cool, and well-ventilated place, away from direct sunlight and other sources of heat and ignition. Storage temperature: +5°C to +35°C (room temperature recommended). Expiration date: 2 years from the date of production. The production date is located on the bottom of the packaging.

With the publication of this data sheet, all previous editions become invalid. Release: 02.25

The product information contained in the technical data sheet is the result of conducted research. With regard to the possibility of using the product (point 3 of this technical data sheet), they should be treated only as recommendations resulting from the manufacturer's experience. Due to the numerous application possibilities and a wide range of work methods using the product, the Manufacturer does not bear any responsibility in this respect, and in particular is not responsible for the consequences of improper use of the product or the effects of work involving the product. Product information is valid only in its most current version.

RYTM TRADE Sp. z o.o.
ul. Strefowa 14
43-100 Tychy | Poland
Tel.: +48 32 324 00 60 /61

WWW.RYTMTRADE.COM