

LIGHT MAINTENANCE LUBRICANT

PRODUCT DESCRIPTION

Universal, lightweight, multi-purpose grease based on mineral oil for the following applications: lubrication, cleaning, corrosion protection, and rust removal.

APPLICATION

- › Loosens seized or stuck parts and protects against corrosion;
- › Locks, hinges, cylinders, rollers, springs and metal guides move smoothly;
- › Protects, lubricates, and preserves sensitive parts of power tools, garden machinery, window fittings, and sectional garage doors;
- › It can also be used for cleaning and maintaining precision mechanical devices and machines;
- › Loosens rusty screws, pipe fittings, nuts, joints, Bowden cables, shafts, locks, etc.;
- › Prevents corrosion of metals and electrical assemblies, cable connections, relays, plugs, connectors, etc., and icing of lock cylinders and locks;

PRODUCT PROPERTIES

- › Universal and versatile use;
- › Lubricates, loosens rust, dissolves dirt and preserves;
- › Protects against corrosion;
- › Keeps moving parts in working order;
- › Neutral towards plastics, paints, metals and wood;
- › Reduces friction and wear;
- › Improves electrical conductivity;
- › Acid-free and silicone-free

TECHNICAL PARAMETERS

State of matter	aerosol, liquid
Colour	transparent, yellowish
Smell	characteristic
Density	0,76 - 0,83 g/cm ³

Technical Data Sheet (TDS)
LIGHT MAINTENANCE LUBRICANT

Temperature resistance:	-30°C - +130 °C
Solubility:	
a) in the water	insoluble
b) in organic solvents	soluble

The above table is for informational purposes only

DELIVERY FORM | PACKAGE

Can, 150 ml

DIRECTIONS FOR USE

Before use, read the product label. Shake the can vigorously before use. For optimal results, first mechanically clean the affected area to remove any dirt. Apply a thin, even layer to the surfaces to be lubricated or protected. Allow to work, depending on the required penetration depth. Repeat application if necessary.

CAUTION! Do not use the product on hot surfaces or components connected to a power source. Remember to disconnect devices from the mains when using the product and, before reconnecting them to the mains, blow out closed systems with compressed air. Test plastic components for surface resistance to the product.

STORAGE AND EXPIRY DATE

The product should be stored in a closed container, upright, in a dry, cool, and well-ventilated place, away from direct sunlight and other sources of heat and ignition. Storage temperature: +5°C to +35°C (room temperature recommended). Expiration date: 2 years from the date of production. The production date is located on the bottom of the packaging.

With the publication of this data sheet, all previous editions become invalid. Release: 03.25

The product information contained in the technical data sheet is the result of conducted research. With regard to the possibility of using the product (point 3 of this technical data sheet), they should be treated only as recommendations resulting from the manufacturer's experience. Due to the numerous application possibilities and a wide range of work methods using the product, the Manufacturer does not bear any responsibility in this respect, and in particular is not responsible for the consequences of improper use of the product or the effects of work involving the product. Product information is valid only in its most current version.

RYTM TRADE Sp. z o.o.
ul. Strefowa 14
43-100 Tychy | Poland
Tel.: +48 32 324 00 60 /61

WWW.RYTMTRADE.COM