

UNIVERSAL DEGREASER

PRODUCT DESCRIPTION

High-quality, special cleaner for industry, automotive, and crafts based on aliphatic hydrocarbons, isopropyl alcohol, and orange terpenes. Perfect for industrial use. Removes protective preservatives, adhesives, and other heavy soiling.

APPLICATION

- › Special combination of solvents for easy and safe cleaning and degreasing;
- › Very strong cleaning and dissolving action, even on stubborn stains, removes adhesive tape residue, marking dyes, protective preservatives, grease, and oil stains;

PRODUCT PROPERTIES

- › Strong cleaning and dissolving action;
- › User friendly;
- › Very good material compatibility - does not contain acetone;
- › High effectiveness thanks to active cleaning agents;
- › Compatible with materials - aluminum, brass, stainless steel, rubber, plastic.
- › Acetone-free

TECHNICAL PARAMETERS

Colour	transparent
Smell	characteristic
State of matter	aerosol, liquid
Density	0,79 ± 0,05 g/cm ³
Temperature resistance	-20°C ÷ +35°C
pH value	not applicable
Solubility:	
a) in the water	insoluble
b) in organic solvents	soluble

The above table is for informational purposes only



Technical Data Sheet (TDS) UNIVERSAL DEGREASER

DELIVERY FORM | PACKAGE

Can, 500 ml

DIRECTIONS FOR USE

Before use, read the product label. Ensure good ventilation in the work area. Shake the container vigorously before use. Spray on the parts to be cleaned, let it act for a moment, and wipe with a clean, dry cloth. For sensitive surfaces, spray onto a cloth and wipe. Repeat if heavily soiled.

STORAGE AND EXPIRY DATE

The product should be stored in a closed container, upright, in a dry, cool, and well-ventilated place, away from direct sunlight and other sources of heat and ignition. Storage temperature: +5°C to +35°C (room temperature recommended). Expiration date: 2 years from the date of production. The production date is located on the bottom of the packaging.

With the publication of this data sheet, all previous editions become invalid. Release: 11.24

The product information contained in the technical data sheet is the result of conducted research. With regard to the possibility of using the product (point 3 of this technical data sheet), they should be treated only as recommendations resulting from the manufacturer's experience. Due to the numerous application possibilities and a wide range of work methods using the product, the Manufacturer does not bear any responsibility in this respect, and in particular is not responsible for the consequences of improper use of the product or the effects of work involving the product. Product information is valid only in its most current version.

RYTM TRADE Sp. z o.o.
ul. Strefowa 14
43-100 Tychy | Poland
Tel.: +48 32 324 00 60 /61

WWW.RYTMTRADE.COM